



HP1X / P1X

The company named below has been authorized by Canadian Standards Association to represent the products listed in this record as "CSA Certified" and to affix the CSA Mark -  - to these products according to the terms and conditions of the CSA Service Agreement.

022354X0000 October 29, 1993(Replaces:September 20, 1993)

CLASS 3238 01 (Re-examination Service)

Page 2

Class I, Groups C and D; Class II, Groups E, F and G; Class I, Division 2, Groups A, B, C and D

Class II, Division 2, Groups E, F and G:

- Pressure operated switches, Model Nos HP1X, followed by AA, HH, CC or GH followed by 15 through 1600 (mwp 1600 psi) with or without suffix SS, followed by P1 through P10, with or without suffix UL and/or B,N,T or V, and/or Q1 through Q99.

Class I, Groups C and D; Class II, Groups E, F and G:

- Pressure-operated switches, Model No P1X, followed by B, F, H, J, K or M, followed by 15 through 1600 (MWP 1600 psi), with or without Suffix SS, followed by P1 through P10, with or without Suffixes UL and/or B, N, T or V, with or without suffix Q1 through Q99 and/or FX.

Note: Switch ratings.

Suffix	Rating
A	10A, 125, 250, 480V ac
B, F, K	15A, 125, 250, 480V ac; 2A, 600V ac; 1/2A, 125V dc; 1/4A, 250V dc
C, M, X	15A, 125, 250, 480V ac; 1/2A, 125V dc; 1/4A, 250V dc.
E	15A, 125, 250, 480V ac; 10A, 125V ac "L"; 1/2A, 125V dc; 1/4A, 250V dc
H, L, J	15A, 125, 250, 480V ac
GH	1A, 125V ac
S	20A, 125, 250, 480V ac
Q1 through Q99	Minor construction and/or identification changes
AA	4A, 250V ac
HH	5A, 250V ac
CC	11A, 1/4 hp, 125/250V ac; 5A-30V dc
GH	5A, 250V ac

Hermetically sealed switches:

Part Number	Rated
1SM314-H2	5A, 250V ac
11SM703-H2	4A, 250V ac
11SM401-H2	5A, 250V ac
41SM1-H2	11A, 1/4 hp, 125/250V ac; 5A-30V dc

(Cont'd)