




The company named below has been authorized by Canadian Standards Association to represent the products listed in this record as "CSA Certified" and to affix the CSA Mark  to these products according to the terms and conditions of the CSA Service Agreement.

022354X0000 October 29, 1993(Replaces:September 20, 1993)

CLASS 3238 01 (Re-examination Service)

Page 4

Note: Suffix letters AA, HH, CC or GH denote different switches with ratings as follows (reduced ratings may be used):

AA	4A at 250V ac
HH	5A at 250V ac
CC	11A, 1/4 hp, 125/250V ac; 5A-30V dc
GH	5A at 250V ac

- Piston operated switches - Model HP1H (CSA Encls. 2, 3, 4 and 5) followed by Suffixes AA, HH, CC or GH followed by 15 through 1600, may be followed by SS, and/or P1 through P15, and/or Q1 through Q99, and/or V, and/or T and/or FX.

Note: Suffix letters AA, HH, CC and GH denote different switches with ratings as follows (reduced ratings may be used):

AA	4A at 250V ac
HH	5A at 250V ac
CC	11A, 1/4 hp, 125/250V ac; 5A-30V dc
GH	5A at 250V ac

- Bourdon tube operated switches, Model Nos HB1T-XY-C and HB2T-XY-C, weather proof and watertight enclosure; Piston operated switches, Model HP1H-XY-C (CSA Encls. 2, 3, 4 and 5); rated 5A max, 250V ac; 11A max, 1/4 hp, 125/250V ac; 5A max, 30V dc.

Note: Suffix X can be a letter A, B, C, H or G, denoting switch type. Suffix Y can be any number 1 to 5, denoting pressure range (psi).

Class I, Div. 2, Groups A, B, C and D; Class II, Div. 2, Groups F and G:

- Diaphragm operated switches, Models Nos HD1H-XY-C and HD2H-XY-C, general purpose enclosure with free leads, Model Nos HDPD1T-XY-C and HDPD2T-XY-C, general purpose enclosure with terminal block; rated 5A max, 250V ac; 11A max, 1/4 hp, 125/250V ac; 5A max, 30V dc.

Note: Suffix X can be a letter A, B, C, H or G, denoting switch type Suffix Y can be any number 1 to 5, denoting pressure range (psi).