

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Pressure Switch**with type designation(s)
B1T, B2T Series

Issued to

Barksdale GmbH
Reichelsheim (Wetterau), Hessen, Germany

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft**Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**

Temperature	D
Humidity	B
Vibration	A
EMC	B
Enclosure	C (IP65)

Issued at **Hamburg** on **2019-10-16**for **DNV GL**This Certificate is valid until **2024-10-15**.DNV GL local station: **Augsburg**Approval Engineer: **Holger Jansen**

Joannis Papanuskas
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Product description

Bourdon Tube Pressure Switch B1T, B2T Series

Type	Range [bar]	Switching diff. [bar]	Test pressure [bar]
B1(2)T-x-12-GL	3,5 – 85	0.7 – 1.5	124
B1(2)T-x-12SS-GL	3.5 – 85	0.8 – 1.9	124
B1(2)T-x-32-GL	11 – 225	1.0 – 2.1	331
B1(2)T-x-32SS-GL	11 – 225	1.0 – 2.4	331
B1(2)T-x-48SS-GL	17 - 340	2.8 – 6.0	496

"x" – switch type: B, H, J, K, M, GB, GH, GM, AA, HH

Output: 1 c/o-contact (B1T..), 2 c/o-contacts (B2T..)

Contact rating: typical values (H, J, M) 125 – 250 Vac /10A
6 – 24 Vdc / 0.5 A

Bourdon Tube:

Bronze = represents Phosphor Bronze Tube with SAE Brass Socket
316 = represents Stainless Steel Tube Socket

Application/Limitation

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV GL, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV GL rules for classification of ships Pt.4 Ch.9 Control and monitoring systems.

Type Approval documentation

Data sheets: B1T/B2T; 923-1496 Rev. H
Drawings: 923-0309 Rev. G (pages 7 + 12)
Operating characteristics HI-P Dia-Seal Piston Models
Assembly Dwg. No. C98148
Technical documentation 7.500 4.70
Test reports: Environmental test report 081070 / 130171
VDE Nr. 19375-9000-4001/A1A
Type Approval Assessment Report 2019-10-08

Tests carried out

Applicable tests according to DNVGL-CG-0339, November 2016.

Marking of product

The products to be marked with:

- Model name
- Manufacturer name
- Serial number

Job Id: **262.1-032364-1**
Certificate No: **TAA00002GJ**

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE