



NKPZ.E42816 Motor Controllers, Float- and Pressure-operated

[Page Bottom](#)

Motor Controllers, Float- and Pressure-operated

[See General Information for Motor Controllers, Float- and Pressure-operated](#)**BARKSDALE INC**

E42816

3211 FRUITLAND AVE
LOS ANGELES, CA 90058 USA

Enclosed type, Pressure-operated switches, "Series 8000", Model(s) 8 followed by one number 1..4 or a letter A..G, followed by one number 1..6 or a letter A..F, followed by 1..8, followed by two letters and one number or one letter (CA3 or P), (CD1 or C), maybe followed by the letter B, V, N, E, S maybe followed by the suffixes HD, (VA or S), W, (LH or L), Q# OR S# or UL.

Enclosed type, Pressure-operated switches, Model(s) 0417 (!), 0427 (!), 0428 (!)

Cat. No. BPS3, followed by 1, 2, 3, 4, or 5, followed by 1, 2, 3, E, G, or N, followed by E or V, followed by M, followed by a number 0 to 9000, followed by Alphanumeric Codes, may be followed by PA

SW2000, SW2000UL, UDS7UL

Pressure and vacuum switches, Model(s) CD or VCD, followed by 1H or 2H, followed by A, B, C, F, H, GH, J, K or M, followed by 2, 3, 18, 80 or 150, may be followed by SS, B1-B10, F3, FX, P1-P10, Q1-Q99Q, S#, Z1 or W. May be followed by additional numbers and suffixes

CDDP or VCDPD, followed by 1H or 2H, followed by A, B, C, F, GH, H, J, K or M, followed by 3, 18, 80 or 150, may be followed by SS, F3, FX, B1-B10, P1-P10, Q1-Q99Q, S#, Z1 or W. May be followed by additional numbers and suffixes.

Pressure switches, Model(s) 9048, 9048S#

B1T, B2T, followed by A, B, C, E, F, GH, H, J, K, L, M, S, or X, followed by 12, 32, 48, 65, or 72 and may be followed by suffix FX, or P1-P10, or S#, or Q1-Q99, and suffix CS

C-9612, C-9612#S, C-9622, C-9622#S, T7, TC-9048, TC-9048S#, TC-9612, TC-9622, TC-9622#S, UDS3UL

Pressure-operated switches, Model(s) 9617, followed by -3, -4, -5 or -6, may be followed by FX, S# or Z1

96200, T96201, T96201, T96211, T9623, 96210, 96210, 96211, 96220, 96221 followed by BB, CC or GH, followed by -1, -2, -3 -4, -5 or -6, may be followed by SS, followed by -T4, -T5 or -T6, may be followed by S#, Z1, Z12, W or P1-P10. Catalog numbers may be followed by additional suffixes.

D1H-, D2H-, D1T- followed by U and D3H-, followed by AA, A, B, C, E, F, H or GH, followed by 2, 3, 18, 80 or 150, may be followed by SS, B1-B10, FX, P1-P10, Q1-Q99, S#, Z1 or W

E1H with suffix letters B, F, GH, H, J, K, M or R, followed by suffix numbers 15, 20, 90, 250, 500 or VAC, with or without additional suffix letters S#, Z1, N, T or V, with or without suffix U, with or without suffix -F2, FX, with or without suffix -BR, -PLS, -P6, S#, Z1 may be followed by Q1-Q99

(!) - followed by blank or LA followed by 00001-99999

Note - All product may be followed by additional numbers and letters.

[Last Updated on 2014-06-27](#)

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".

NKPZ7.E42816

Motor Controllers, Float- and Pressure-operated Certified for Canada

[Page Bottom](#)

Motor Controllers, Float- and Pressure-operated Certified for Canada

[See General Information for Motor Controllers, Float- and Pressure-operated Certified for Canada](#)

BARKSDALE INC

E42816

3211 FRUITLAND AVE
LOS ANGELES, CA 90058 USA

Enclosed type, Pressure-operated switches, "Series 8000", Model(s) 8 followed by one number 1..4 or a letter A..G, followed by one number 1..6 or a letter A..F, followed by 1..8, followed by two letters and one number or one letter (CA3 or P), (CD1 or C), maybe followed by the letter B, V, N, E, S maybe followed by the suffixes HD, (VA or S), W, (LH or L), Q# OR S# or UL.

Enclosed type, Pressure-operated switches, Model(s) 0417 (!), 0427 (!), 0428 (!)

Cat. No. BPS3, followed by 1, 2, 3, 4, or 5, followed by 1, 2, 3, E, G, or N, followed by E or V, followed by M, followed by a number 0 to 9000, followed by Alphanumeric Codes, may be followed by PA

SW2000, SW2000UL, UDS7UL

Pressure and vacuum switches, Model(s) CD or VCD, followed by 1H or 2H, followed by A, B, C, F, H, GH, J, K or M, followed by 2, 3, 18, 80 or 150, may be followed by SS, B1-B10, F3, FX, P1-P10, Q1-Q99Q, S#, Z1 or W. May be followed by additional numbers and suffixes

CDPD or VCDPD, followed by 1H or 2H, followed by A, B, C, F, GH, H, J, K or M, followed by 3, 18, 80 or 150, may be followed by SS, F3, FX, B1-B10, P1-P10, Q1-Q99Q, S#, Z1 or W. May be followed by additional numbers and suffixes.

Pressure switches, Model(s) 9048, 9048S#

B1T, B2T, followed by A, B, C, E, F, GH, H, J, K, L, M, S, or X, followed by 12, 32, 48, 65, or 72 and may be followed by suffix FX, or P1-P10, or S#, or Q1-Q99, and suffix CS

C-9612, C-9612#S, C-9622, C-9622#S, T7, TC-9048, TC-9048S#, TC-9612, TC-9622, TC-9622#S, UDS3UL

Pressure-operated switches, Model(s) 9617, followed by -3, -4, -5 or -6, may be followed by FX, S# or Z1

96200, T96201, T96201, T96211, T9623, 96210, 96210, 96211, 96220, 96221 followed by BB, CC or GH, followed by -1, -2, -3 -4, -5 or -6, may be followed by SS, followed by -T4, -T5 or -T6, may be followed by S#, Z1, Z12, W or P1-P10. Catalog numbers may be followed by additional suffixes.

D1H-, D2H-, D1T- followed by U and D3H-, followed by AA, A, B, C, E, F, H or GH, followed by 2, 3, 18, 80 or 150, may be followed by SS, B1-B10, FX, P1-P10, Q1-Q99, S#, Z1 or W

E1H with suffix letters B, F, GH, H, J, K, M or R, followed by suffix numbers 15, 20, 90, 250, 500 or VAC, with or without additional suffix letters S#, Z1, N, T or V, with or without suffix U, with or without suffix -F2, FX, with or without suffix -BR, -PLS, -P6, S#, Z1 may be followed by Q1-Q99

(!) - followed by blank or LA followed by 00001-99999

Note - All product may be followed by additional numbers and letters.

[Last Updated on 2014-06-27](#)

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".